

DS-K1T802 Series

Access Control Terminal

AVAILABLE MODELS

- DS-K1T802E (EM Card Only)
- DS-K1T802M (M1 Card Only)



MAIN FEATURES

- 32-bit processor
- Stand-alone operation management settings
- Supports offline working, and online upgrade
- Max. 3000 card number settings, and Max. 10000 event records
- Supports Mifare card recognition, and Mifare card number reading (DS-K1T802M)
- Supports ID card recognition, and ID card number reading (DS-K1T802E)
- 128×64 Dot Matrix STN screen for displaying time, date, and week
- Supports TCP/IP network communication
- Multi-authentication mode: card, card and password
- Supports exit button
- Supports duress alarm function, and self-defined duress password(card)
- Supports first card, remote open door, super card and super password. Super password would not be restricted by the schedule template. Super card must observe the permission schedule (excepts the NC status)
- Supports offline event alarm for insufficient storage, offline alarm, door unsecured alarm, force opening door alarm, door opening time out alarm etc.
- Supports self-defined number for eliminating alarm
- Supports multi types of card: normal/disabled/blacklist/patrol/super/duress
- Supports time synchronization via NTP, manual or automatic method
- Watchdog design
- Data can be permanently saved after power-off
- Client supports attendance function

SPECIFICATIONS

Model	DS-K1T802E		DS-K1T802M
Parameters			
Processor	32bit		
Storage	Storage for 3000 Legal Card Information and 10,000 Event Records		
Communication type	TCP/IP		
Card type	EM Card	Mifare Card	
Input interface	Exit Button × 1, Door Sensor × 1		
Output interface	Doorbell × 1, E-lock Output × 1		
Key board	13 Keys (0-9, *, #, Doorbell)		
Display screen	STN Screen (Resolution 128*64)		
LED Indicator	Communication/Status		
Voice prompt	Beeper		
Working voltage	12V DC		
Working current	0.17 A(without Load)		
Working Temperature	-20°C to 65°C (-4° F to 149° F)		
Working Humidity	10% to 90% (No Condensing)		
Dimension	126.5(L)mm×94.5(W)mm×24(H)mm (4.98" × 3.72" × 0.94")		