



The **PHASAK Essential** series with interactive technology allows you to know at all times from the time the batteries are charged.

It allows advanced management of the UPS through the USB HID port from any computer with a USB socket and has protected RJ45 sockets, which offer protection against surges and electrical

Data Sheet

Referencia	PH 9464	PH 9465	PH 9485	PH 9410	PH 9420
Power	600 VA / 360 W	650 VA / 360 W	850 VA / 480 W	1000 VA / 600 W	2000 VA / 1200 W
Input					
Rated Voltage	220 / 230 / 240 Vac				
Voltage Range	162 - 290 Vac				
Frequency	50 Hz / 60 Hz (Auto detection)				
Salida					
Voltage Regulation (Bat.)	220 - 240 Vac				
Frequency (Bat.)	50 Hz / 60 Hz ± 1%				
Waveform (Bat.)	Simulated sinusoidal	Modified sinusoidal	Modified sinusoidal	Simulated sinusoidal	Simulated sinusoidal
Transfer time	2 - 6 ms				
Overload protection	Circuit breaker or internal protection fuse				
Battery					
Quantity / Tipe / n°	1x 12V / 7 Ah	1x 12V / 7 Ah	1x 12V / 9 Ah	2x 12V / 7 Ah	2x 12V / 9 Ah
Charging time (90%)	8 h	4 - h	4 - h	6 h	6 h
Indicators					
Display	LCD Táctil	LCD	LCD	LCD Táctil	LCD Táctil
Alarmas	Battery On / Battery Low / Overload / Fault				
Características					
Dimensions (WxHxD)	279 x 101 x 142	287 x 100 x 142	287 x 100 x 142	350 x 146 x 205	350 x 146 x 205
Weight (Kg)	4.2	4.25	4.90	8.2	11.0
Operating humidity	0 - 90 % without condensation				
Operating temperature	0 - 40°C				
<i>Specifications subject to change without notice. PHASAK® copyrights.</i>					