

# CD 470

## Shock sensor



### Technical data

Approvals	EN 50131-2-8 Grad 3, SBSC Class 3, VdS G 121502 Class B, F&P Danmark
Input voltage	8 – 15 VDC (DAY), 6 VDC (NIGHT)
Alarm output	Relay (Max 50V / 120 mA), R up to 30 Ω
Alarm indication	LED, DAY/NIGHT controlled
Alarm hold time	4s (auto reset) or locks in alarm mode
Alarm reset	Voltage breaking input (up to 1 V)
Operating temperature range	-40°C - +55°C
Housing material, Colour	ABS Plastic, white
Housing protection class	IP 42
Dimensions (L x W x H) mm	80 x 23 x 20 mm
Tamper output relay	Relay (Max 50V / 120 mA), R up to 30 Ω
Detection radius	up to 3m
DAY and NIGHT control	DAY 8V, NIGHT 6V supply voltage
Low voltage alarm or fault in electronics	up to 5V is indicated by flashing LED
Current consumption quiescent / alarm	8.0 mA (12 V)/7.1 mA (12 V)
Grade	3



CD 470 offers reliable monitoring against attacks with mechanical tools. The CD 470 is a chock- and vibration sensor with 3 separate detection channels: an integration channel / saw channel for weak signals with long duration, a counting channel that senses strong impact on the monitored surface and an explosion channel which senses very strong signals from e.g. an explosion.

CD 470 shares design with CD 475 but has built-in relays for the alarm and tamper outputs. This allows the CD 470 to be connected directly to the alarm central unit, this means that no analyser unit is necessary. CD 470 polarity independent, just like CD 475.

### FEATURES

- Relay outputs for alarm and tamper
- Two wire polarity independent for easy connection
- 3 separate detection channels
- Cover radius up to 3m
- Resistant to interference
- Detailed sensitivity setting
- Suitable for 24 hour monitoring
- DAY and NIGHT control of LED

**Related products and accessories****MP 550**

Mounting Plate  
for CD 550